

CCTV CAMERA PRODUCT

DATA TEST SHEET SAMPLE (PROVIDED WITH EACH CSI-12M-CCTV)

Cable ID: CAT6 Channel with Lifter 629223



Test Summary: PASS

Headroom 8.8 dB (NEXT 36-45)
 Test Limit: Aus/NZ Channel Class D
 Cable Type: Cat 6 UTP
 Calibration Date: 06/03/2013

Software Version: 2.7400
 Limits Version: 1.9300
 NVP: 69.0%



Model: DTX-1200
 Main S/N: 8662009
 Remote S/N: 8662010
 Main Adapter: DTX-CHA001
 Remote Adapter: DTX-CHA001

Length (m)	[Pair 36]	85.8
Prop. Delay (ns), Limit 55	[Pair 45]	435
Delay Skew (ns), Limit 50	[Pair 45]	20
Resistance (ohms), Limit 25.0	[Pair 78]	18.9
Insertion Loss Margin (dB)	[Pair 45]	6.9
Frequency (MHz)	[Pair 45]	100.0
Limit (dB)	[Pair 45]	24.0





Worst Case Margin Worst Case Value



PASS	MAIN	SR	MAIN	SR
Worst Pair	36-45	36-45	36-78	36-45
NEXT (dB)	18.4	8.8	20.7	9.1
Freq. (MHz)	8.4	83.0	98.8	99.3
Limit (dB)	48.3	31.5	30.2	30.1
Worst Pair	36	36	78	36
PS NEXT (dB)	18.2	11.0	21.3	11.2
Freq. (MHz)	7.1	49.0	99.0	99.8
Limit (dB)	46.4	32.4	27.2	27.1





PASS	MAIN	SR	MAIN	SR
Worst Pair	36-12	36-12	45-12	12-45
ACR-F (dB)	19.5	19.5	21.8	21.6
Freq. (MHz)	3.0	3.0	100.0	100.0
Limit (dB)	47.9	47.9	17.4	17.4
Worst Pair	12	12	45	12
PS ACR-F (dB)	20.8	21.0	22.9	23.7
Freq. (MHz)	3.6	6.1	98.5	100.0
Limit (dB)	43.2	38.7	14.5	14.4



PASS	MAIN	SR	MAIN	SR
Worst Pair	36-45	36-45	36-78	36-45
ACR-N (dB)	15.9	12.3	27.9	15.9
Freq. (MHz)	2.3	13.4	98.8	99.5
Limit (dB)	53.6	36.6	6.3	6.2
Worst Pair	36	36	78	45
PS ACR-N (dB)	15.4	14.9	28.5	18.5
Freq. (MHz)	2.3	9.9	99.0	99.3
Limit (dB)	50.6	37.0	3.3	3.2



PASS	MAIN	SR	MAIN	SR
Worst Pair	45	36	45	36
RL (dB)	4.0	1.4	8.6	1.4
Freq. (MHz)	20.3	91.0	67.0	95.3
Limit (dB)	16.9	10.4	11.7	10.2



Compliant Network Standards:
 10BASE-T 100BASE-TX 100BASE-T4
 1000BASE-T ATM-25 ATM-51
 ATM-155 100VG-AnyLan TR-4
 TR-16 Active TR-16 Passive

LinkWare Version 8.0

Project: LMS

Site: LMS

